

PLUSWINCH

> Assembly & Operation Guide for brackets & mounting

> Contents

PORTAGANTRY RAPIDE® 500	4
PORTAGANTRY RAPIDE* 1000	6
PORTAGANTRY' Small & Medium	8
Fitting device into Bracket	10
PORTAGANTRY"	12
TDAVIT*	14
PORTADAVIT QUANTUM* Column	16
PORTADAVIT QUANTUM* Backstay	18
PORTADAVIT° 500	20
PORTX*DAVIT	22



Lightweight. Portable. Safe.

Please read the following instructions and guidance notes carefully. These have been designed to aid users in carrying out the correct assembly of the bracket for each of our compatible lifting systems. Systems compatible with this product are:

- > PORTAGANTRY RAPIDE
- > PORTAGANTRY*
- > TDAVIT
- > PORTADAVIT QUANTUM"
- > PORTADAVIT
- > PORTX*DAVIT

General Specification

- > Maximum rated capacity for goods lifting 500kg
- > Ensure the rating of the Winch is always checked before use
- > For use with REID lifting products only

Standards

> EN13157:2004+A1:2009

For further information please refer to the technical data sheet for this product.


> Assembly Instructions: PORTAGANTRY RAPIDE® 500

The following instructions detail the assembly of the PlusWinch bracket [RAWB010220] for the PORTAGANTRY [RAWB010220] for the PORTAG




PlusWinch Bracket - [RAWB010220]


Assembling the **PlusWinch Bracket** on **PORTA**GANTRY RAPIDE 500




> Remove the existing top bolt.



Insert the new, longer bolt leaving it loose so that the head sits proud of the plate.



> Hook the brakcet over the bolt head.



> Straighten the winch and insert the lower pin.



> Fully tighten both the top bolt and bottom pin. The winch bracket should sit flush with the plate.



You may now route the cable as normal and use the winch.


> Assembly Instructions: PORTAGANTRY RAPIDE® 1000

The following instructions detail the assembly of the PlusWinch bracket [RAWB010220] for the PORTAGANTRY [MADE] 1000kg,




PlusWinch Bracket - [RAWB010220]


Assembling the **PlusWinch Bracket** on **PORTA**GANTRY RAPIDE 1000




> Insert the new, longer bolt leaving it loose so that the head sits proud of the plate.



Hook the brakcet over the bolt head.



> Straighten the winch and insert the lower pin.




> Fully tighten both the top bolt and bottom pin. The winch bracket should sit flush with the plate.



You may now route the cable as normal and use the winch.


> Assembly Instructions: PORTAGANTRY® S & M

The following instructions detail the assembly of the PlusWinch bracket [RAWB010225] for the PORTAGANTRY' Small and Medium frame sizes.




PlusWinch Bracket - [RAWB010225]

Assembling the **PlusWinch Bracket** onto a small or medium **PORTA**GANTRY*



Insert the bolt into the top hole and secure using the knurled knob, leaving it loose so that the head sits proud of the plate.



Hook the brakcet over the bolt head.



> Straighten the winch and insert the lower pin.




> Fully tighten both the top bolt and bottom pin. The winch bracket should sit flush with the plate.



You may now route the cable as normal and use the winch.


Assembly Instructions: Fitting the Device

The following instructions detail the assembly of the PlusWinch device into the universal bracket.



PlusWinch Bracket

Assembling the **PlusWinch** onto the connecting plate.



Remove the washers and nyloc nuts from the bracket.



> Present the device to the bracket.



> Adjust the position by tightening the hex bolts.



> The device is now ready to use.

Now install the product into the column or backstay.

The following instructions detail the assembly of the PlusWinch bracket [RAWB010208] for the PORTAGANTRY'.




PlusWinch Bracket - [RAWB010208]


Assembling the **PlusWinch Bracket** onto a **PORTA**GANTRY*



The bracket comes with the pins supplied, as shown above.



> Remove the pins and present the bracket to the winch column, aligned to the holes as shown.



 Insert both pins to ensure the bracket is securely attached.



The following instructions detail the assembly of the PlusWinch bracket [RAWB010200] for the TDAVIT.




Protective Egeture

PlusWinch Bracket - [RAWB010200]


Assembling the **PlusWinch Bracket** onto a $TDAVIT^*$



The bracket comes with the pins supplied, as shown above.



> Remove the pins and present the bracket to the column, aligned to the holes as shown.



 Insert both pins to ensure the bracket is securely attached.



> Assembly Instructions: PORTADAVITQUANTUM® Column.

The following instructions detail the assembly of the PlusWinch bracket [RAWB010200] for the **PORTA**DAVIT@@@num. **Warning:** For this configuration a sheave bracket column is required.




PlusWinch Bracket - [RAWB010200]

Assembling the **PlusWinch Bracket** onto a **PORTA**DAVITQUANTUM® column.



> The bracket comes with the pins supplied, as shown above.




> Remove the pins and present the bracket to the column, aligned to the holes as shown.




 Insert both pins to ensure the bracket is securely attached.



> Present the sheave bracket* to the top of the column, aligning wth the top holes as shown.



> Secure using the pins provided.



The bracket is secured and ready for the device to be attached.

*RAW000095 - Sheave bracket PDQ Column Medium Sheave (4-7mm).

> Assembly Instructions: PORTADAVITQUANTUM® Backstay.

The following instructions detail the assembly of the PlusWinch bracket [RAWB010206] for the PORTADAVITIGUARDIN BACKSTAY.




PlusWinch Bracket - [RAWB010206]


Assembling the **PlusWinch Bracket** onto a **PORTA**DAVITQUANTUM® Backstay.




The bracket comes with the pins supplied, as shown above.



> Remove the pins and present the bracket to the backstay, aligned to the holes as shown.



 Insert both pins to ensure the bracket is securely attached.



The following instructions detail the assembly of the PlusWinch bracket [RAWB010203] for the PORTADAVIT 500.



PlusWinch Bracket - [RAWB010203]

Assembling the **PlusWinch Bracket** onto a **PORTA**DAVIT 500.



The bracket comes with the pins supplied, as shown above.




> Remove the pins and present the bracket to the backstay, aligned to the holes as shown.



Insert both pins to ensure the bracket is securely attached.



The following instructions detail the assembly of the PlusWinch bracket [RAWB010200] for the PORTX DAVIT.




Protective Egoture

PlusWinch Bracket - [RAWB010200]


Assembling the **PlusWinch Bracket** onto a **PORTX*** DAVIT with a Single Winch.




The bracket comes with the pins supplied, as shown above.



> Remove the pins and present the bracket to the column, aligned to the holes as shown.



 Insert both pins to ensure the bracket is securely attached.



Contact Us

Head Office, UK

Unit 1 Wyeview Newhouse Farm Industrial Estate Chepstow Monmouthshire NP16 6UD United Kingdom

- > +44 (0)1291 620 796
- > enquiries@reidlifting.com
- > www.reidlifting.com

All information herein is copyright protected by REID Lifting Ltd. All company and product names are Trade Mark and Trade Name protected and all REID Lifting Ltd. Product IPR is protected under Patents, Patents Pending and/or Design Rights.

Printed using environment friendly processes and materials.